



PCB LAYOUT
(Top View)

RoHS
Compliant

SPECIFICATION :

1. Electrical Char.

Insulation Resistance : 500M-Ohm Min. 500V DC. for 1 minute

Contact Resistance : 30milli-Ohm Max.

Rating Current : 1.5A Max.

Rating Voltage : 150V AC.

Dielectric Voltage : 1,000 Vrms at 1MA 60 Sec. Min.

2. Physical char.

Housing :

PBT Glass Filled Black (UL 94V-0)

Spring Wire:

0.45mm Dia. Phosphor Bronze Gold Plating Over Nickel

Temperature Range : - 40° ~ +85°C

Durability : 750 Mating cycles Min.

ORDER INFORMATION

AMJ-26XRDXX 145-72

A: Single Row
M: Reverse Type
J: Jack
D: DIP
R: Right Angle
Port Number
Pin Contact
62: 6P2C
64: 6P4C
66: 6P6C
Plating
G1: Gold Flash
G4: 15u"
G5: 30u"
G6: 50u"
G7: 3U"
G8: 6u"

REV.	REVISION RECORD	DATE	General Tolerances			
A	Original	08/20/13'	LINEAR	0.0 ±0.35 0.00±0.20	ANGLES ±3°	
B	Revised	01/29/14'	UNIT: mm		DWG.NO.: AMJ-26XRDXX145-72 REV. B	
			A4	NAME		DATE
			APPROVED	MARTIN		
			DESIGNER	MERLIN		
			DRAWN	ANGEL		