



PIN	A	B	C	D	E
9	30.81	24.99	16.33	19.28	10.72
15	39.14	33.32	24.66	27.65	10.72
25	53.04	47.04	38.38	41.30	10.72
37	69.32	63.50	54.84	57.44	10.72

Note:

- Specification:
 - Contact Resistance: 30mohm Max.
 - Dielectric withstanding voltage: 500V AC
 - Insulation Resistance: 1000Meg ohms Min.

2. Materials:

- Insulator: PBT
- Contact: Copper Alloy
- Shell: SPCC-SD Nickel Plated
- Contact: Gold plating on contact area, Tin on soldering pins

Order Information :

DSSI-F XX A 03 R -59

D-Sub solder female type series
 Pin position
 X: Without any screw and accessories
 A: With screw rivet front side
 03: Gold Flash
 15: Au 15u"
 30: Au 30u"
 R: RoHS

REV.	REVISION RECORD	DATE	General Tolerances					
			LINEAR	0.0 ±0.35	ANGLES			
A	Original	10/18/04'						
				UNIT: mm(in)				
			A4	NAME	DATE	TITLE: D-Sub solder Female with Rivet Front		
			APPROVED	MARTIN		DWG.NO.: DSSI-FXXA03R-59 REV. A		
			DESIGNER	MERLIN		SCALE 1 : 1 SHEET 1 OF 1		
			DRAWN	ANGEL				