

1				2	3	4	5	6	7	8																						
A	Poles	DIM.A	DIM.B	DIM.C				<h1 style="text-align: center;">Ordering Information</h1> <p style="text-align: center;">WC - 4 - XX - XX - E001 - X - 44</p> <table style="width: 100%; border: none;"> <tr> <td style="border: none;">1.0P Wafer</td> <td style="border: none;">1.DIP RA</td> <td style="border: none;">Total PIN</td> <td style="border: none;">Contact Plated</td> <td style="border: none;">Packing</td> </tr> <tr> <td style="border: none;"></td> <td style="border: none;">2.DIP VT</td> <td style="border: none;"></td> <td style="border: none;">PT: TIN</td> <td style="border: none;">3: T&amp;R+cap</td> </tr> <tr> <td style="border: none;"></td> <td style="border: none;">3.SMT RA</td> <td style="border: none;"></td> <td style="border: none;"></td> <td style="border: none;">4: Bag</td> </tr> <tr> <td style="border: none;"></td> <td style="border: none;">4.SMT VT</td> <td style="border: none;"></td> <td style="border: none;"></td> <td style="border: none;"></td> </tr> </table>					1.0P Wafer	1.DIP RA	Total PIN	Contact Plated	Packing		2.DIP VT		PT: TIN	3: T&R+cap		3.SMT RA			4: Bag		4.SMT VT			
	1.0P Wafer	1.DIP RA	Total PIN	Contact Plated									Packing																			
		2.DIP VT		PT: TIN									3: T&R+cap																			
		3.SMT RA			4: Bag																											
	4.SMT VT																															
B	2A	1.00	4.50	2.60			<div style="border: 1px solid black; border-radius: 50%; padding: 5px; display: inline-block;">RoHS Compliant</div>																									
	3A	2.00	5.50	3.60																												
	4A	3.00	6.50	4.60																												
	5A	4.00	7.50	5.60																												
C	6A	5.00	8.50	6.60			<p><b>SPECIFICATIONS</b></p> <ul style="list-style-type: none"> <li>Applicable Wire: AWG#28~#32</li> <li>Voltage Rating: 50V AC/DC(rms)</li> <li>Current Rating: 1.0A (AWG#28)</li> <li>Withstand voltage: 500V AC/Min(rms)</li> <li>Working Temperature: -25℃~+85℃</li> <li>Insulation Resistance: ≥100MΩ</li> <li>Contact Resistance: ≤20mΩ</li> </ul> <p><b>MATERIAL</b></p> <ul style="list-style-type: none"> <li>Terminal: Phosphor Bronze</li> <li>Housing: PA9T, UL94V-0</li> <li>Solder Tab: Phosphor Bronze</li> </ul>																									
	7A	6.00	9.50	7.60																												
	8A	7.00	10.50	8.60																												
	9A	8.00	11.50	9.60																												
D	10A	9.00	12.50	10.60																												
	11A	10.00	13.50	11.60																												
	12A	11.00	14.50	12.60																												
	13A	12.00	15.50	13.60																												
E	14A	13.00	16.50	14.60																												
	15A	14.00	17.50	15.60																												
	16A	15.00	18.50	16.60																												
	17A	16.00	19.50	17.60																												
F	18A	17.00	20.50	18.60																												
	19A	18.00	21.50	19.60																												
	20A	19.00	22.50	20.60																												
G																																
H																																

REV.	REVISION RECORD	DATE	General Tolerance			<b>ARIBA</b> TECHNOLOGY CO., LTD.				
A	Original	06/07/13*	LINEAR	ANGLE ±3°						
B	Revised	10/03/13*	0.0 ±0.35 0.00 ±0.20		UNIT:mm		TITLE: 1.0P Wafer SMT Vertical 4.35H DWG.NO: WC4XXXXE001X-44    REV. D			
C	Revised	11/30/15*			A4    NAME    DATE					
D	Revised	06/23/17*	APPROVED		SUNNY					
			DESIGNER		TED					
			DRAWN		WING		SCALE	1:1	SHEET	1 OF 1